

Direct certification of a class of quantum simulations

D. Hangleiter,^{1,2} M. Kliesch,¹ M. Schwarz,¹ and J. Eisert¹

¹*Dahlem Center for Complex Quantum Systems, Freie Universität Berlin, D-14195 Berlin, Germany*

²*Fakultät für Physik, Ludwig-Maximilians-Universität, 80799 München, Germany*

(Dated: February 3, 2016)

One of the main challenges in the field of quantum simulation and computation is to identify ways to certify the correct functioning of a device when a classical efficient simulation is not available. In such a situation one cannot simply classically keep track of the dynamics of the device. In this note, we discuss weak-membership notions of the certification for ground state preparations of frustration-free Hamiltonians based on simple energy measurements of local Hamiltonian terms. These considerations have applications to classically intractable analog quantum simulations: for example, using Feynman-Kitaev Hamiltonians, one can realise universal quantum computers. Our certification approach is non-interactive and thus avoids challenges arising from interactive proof systems. Moreover, our certification protocol is applicable to recent results on so-called IQP circuits aiming at the demonstration of quantum supremacy.

Introduction

Quantum devices offer the promise to outperform classical machines computationally and to solve problems intractable in the classical domain. This idea is most prominent in the idea of a fully-fledged universal quantum computer that could—once physically realised for large system sizes—solve problems like factoring in polynomial time [1]. Indeed, much effort is dedicated to realising the building blocks from which such a universal quantum computer could be built. What is already available with present technology, however, are quantum simulators [2], machines able to simulate other quantum systems, based on an idea going back to Richard Feynman [3]. In particular, this is true for so-called analog quantum simulators that involve a very large number of quantum constituents whose time evolution is not discretised as is the case in digital simulations. Arguably, the most prominent such architecture for analog simulation is based on cold atoms in optical lattices [4], but also promising other platforms such as trapped ions [5] or superconducting qubits [6] are conceivable. As of yet, their computational power is far from clear, though. They are special purpose machines, in that one can achieve a tremendous degree of control, but only over some parameters: In this way, it is perfectly conceivable to prepare ground states of interacting Hamiltonians to probe effects such as high- T_c superconductivity [7] or lattice gauge theories [8]. Equally well, properties of time evolution can be probed in dynamical quantum simulators [9, 10].

In all such approaches the problem of certification arises, providing an answer to the question: *Is the device working precisely in the anticipated fashion?* In case of a decision problem in BQP that solves a problem in NP, one can of course in retrospect efficiently certify the correctness of the solution to the decision problem by classical means. This approach is insufficient in many instances, however. To start with, not all problems interesting to be solved on a quantum device are decision problems. In particular in quantum simulation, a much more pressing question is to find out whether one has achieved the ground state preparation accu-

ately. Then, one would like to have information about intermediate steps of the quantum computation or simulation, and not only at the end of it. If parameter regimes are available that allow for an efficient classical simulation—as is the case, e.g., in non-interacting physical systems—one can set benchmarks in certain regimes. In the physics literature, it is surprisingly common to assume that the only way to certify the correctness of a quantum simulation is to find regimes in which a classical simulation is available.

Notions of verified quantum computation [11–14] address the question of how the correct functioning of quantum machines can be checked. In such approaches, it is usually a small, well-characterised quantum system that is used to certify the functioning of a larger quantum machine making use of the idea of interactive proof systems involving several rounds of interaction between a restricted verifier and a powerful prover. In multi-round systems, the dynamics of a system can even be certified without the need for any quantum mechanical capacities [15, 16]. In the same spirit, it is shown in Refs. [17–19] how trust in a quantum simulator can be amplified to certifying an untrusted simulator or to learning about the Hamiltonian of an unknown system. Very recently, a single-round scheme was devised [13] that relies on preparing the ground state of a Feynman-Kitaev Hamiltonian. Based on the assumption that an energy measurement on such a state “may well be comparable in complexity to independently implementing the circuit to be evaluated” the authors devise a rather sophisticated protocol, which, to an extent, seems to be skew to the conceptual simplicity expected of a quantum simulator.

In this note we address the question of certifying quantum simulations and computations from the perspective of certifying ground states of frustration-free Hamiltonians. We do so by putting known results into a new context [14, 20] and proving some new results. We arrive at a surprisingly stringent and simple paradigmatic setting in which one can unambiguously certify the correct functioning of the device – yet at the same time, the actual outcome of the simulation or quantum computation cannot be predicted classically. In this setting,

merely local Hamiltonian terms have to be measured in order to certify both, quantum simulators, as well as universal quantum computations. To show our result, we make use of the framework of a physically plausible variant of a Feynman-Kitaev Hamiltonian construction. In this sense, we show that the claim cited above not to apply in our setting. Indeed, one can certify a simulation performed in our setting by estimating the energy of ground state preparations. Part of the purpose of this note is to provide a link between the physics and computer science literature, hence contributing to the debate on how to reliably certify quantum simulators outperforming classical machines.

An intriguing application of our certification protocol arises from Ref. [21]. In this work, the authors present a restricted (non-universal) family of *commuting* quantum circuits, where sampling from their output probability distribution with an error in trace distance of less than $1/192$ is *provably hard* for any classical computer up to a plausible complexity-theoretic conjecture, unless the Polynomial Hierarchy (a generalisation of $P \neq NP$) collapses. Since this circuit can be mapped to a frustration-free local Hamiltonian, our methods allow to certify that the experimenter is indeed sampling from a probability distribution within the required bound of $1/192$, which is *provably hard to perform on any classical computer!* Therefore, the combination of our methods with the results of Ref. [21] directly yield an experimental proposal to demonstrate *quantum supremacy* [22].

Notions of quantum simulation

We start by emphasising what properties of quantum simulators we consider indispensable. Except from solving an interesting problem from the physics perspective, a quantum simulator should satisfy the following two criteria: it should be certifiable (reliable), and it should be able to solve a computationally hard problem that cannot efficiently be solved using classical means (proper).

- (i) A quantum simulator should be *proper*. We call a *ground state quantum simulator* (GS-QS) proper if using it one can solve a computational task that is believed to be intractable on a classical computer.
- (ii) A quantum simulator should be *reliable*. We call a GS-QS *reliable* if there exists a weak-membership certification test (Def. 3) by which the actual preparation ρ_p of the ground state can be certified.

Definitions

We now turn to defining key concepts for what follows. We start by defining properties of Hamiltonians relevant for ground state quantum simulations considered here, related to being local, frustration-free and having a Hamiltonian gap.

Definition 1 (*k*-local Hamiltonians). Let Λ be a finite set of sites, and associate with each site $v \in \Lambda$ a finite-dimensional Hilbert space $\mathcal{H}_v$. A Hamiltonian $H = \sum_{\lambda \subset \Lambda} h_\lambda$ defined on $\mathcal{H} = \bigotimes_{v \in \Lambda} \mathcal{H}_v$ is called (*k*-)local if each term h_λ acts on at most $k = O(1)$ sites within λ , i.e., has finite support $|\text{supp}(h_\lambda)| \leq k$ independent of the system size $N = |\Lambda|$.

Throughout, we assume the local terms to be bounded in spectral norm, $\|h_\lambda\| \leq O(1)$ for all λ independent of the system size. Most important will be the situation of encountering spatial locality, where the supports of the h_λ are connected sets on a physical lattice such as a cubic lattice.

Definition 2 (Frustration-free Hamiltonians and gap). A local Hamiltonian $H = \sum_{\lambda} h_\lambda$ with ground-state energy $E_0 = 0$ is called frustration-free (FF), if the projection P_0 onto the ground-state space of H satisfies $HP_0 = 0$ and $h_\lambda P_0 = 0$ for all λ .

A Hamiltonian H is said to be (polynomially) gapped if the energy gap Δ above the ground state – here, just the second smallest eigenvalue of H – satisfies $\Delta = \Delta(N) \propto 1/\text{poly}(N)$.

Certification of proper ground state quantum simulations

We now turn to the actual certification scheme and the main insight of this work: Quantum systems that are described by spatially local, frustration-free and gapped Hamiltonians with unique ground state realise (i) reliable GS-QS some of which are even (ii) proper. In other words, in a realistic physical setting, namely, for systems described by spatially frustration-free gapped Hamiltonians with unique ground state it is indeed possible to solve problems that are believed to be intractable classically. This insight is very much in the original spirit of quantum simulators presumably outperforming classical devices.

To prove that GS-QS with frustration-free and polynomially gapped Hamiltonians with unique ground state is reliable we use that the ground state of such Hamiltonians be certified efficiently by measurements of local Hamiltonian terms only [14, 20]. This is formalised in Proposition 1, where we provide bounds on the required number of measurements given a desired accuracy.

To demonstrate that in the same setting also computationally hard problems can presumably be solved, we make use of the fact that universal quantum computation can be performed by cooling to ground states of frustration-free Hamiltonians [23, 24]. To demonstrate this one needs to show that any quantum computation can be reduced to (local) measurements on that ground state. Specifically, Proposition 2 states that adiabatic quantum computation can be performed efficiently using a polynomially gapped spatially local frustration-free Hamiltonian H_{ac} . Since adiabatic computation (ac) is universal [25], any problem in BQP can be solved using the system described by H_{ac} .

Weak-membership certification

We now define weak-membership quantum state certification. This is at the heart of our notion of certifying the correctness of a preparation. It captures precisely what it means to “have prepared a state to a given accuracy in the laboratory”. It is conveniently conceptualised in terms of a game between a sceptic and restricted certifier Arthur and a powerful but untrusted quantum prover Merlin. Arthur has access to classical computation and spatially local measurements; Merlin is able to prepare arbitrary quantum states of large quantum systems. The input to the game is the classical description of the Hamiltonian H the ground state of which we want to prepare. Merlin prepares a number of independent and identical copies of a quantum state ρ_p . Arthur’s goal is to certify that ρ_p is indeed the ground state of H . In our setting, the only interaction we require between Arthur and Merlin is the local measurements of Arthur on the state preparation given to him by Merlin [14]. The test accepts if the state ρ_p prepared by Merlin is sufficiently close to the actual ground state ρ_0 in fidelity that is given by $F(\sigma, \rho) := \text{Tr}[\rho\sigma]$ for at least one of σ and ρ pure. The fidelity is related to the trace distance $d(\sigma, \rho) = \text{Tr}[|\sigma - \rho|]/2$ via $1 - F(\sigma, \rho)^{1/2} \leq d(\sigma, \rho) \leq (1 - F(\sigma, \rho))^{1/2}$. A robust reading of what it precisely means for Arthur to “certify” ρ_p as a good approximation of ρ_0 in terms of the fidelity is the notion of a weak-membership state certification:

Definition 3 (Weak-membership quantum state certification). *Let $F_T > 0$ be a threshold fidelity and $0 < \alpha < 1$ a maximal failure probability. A test which takes as an input a classical description of ρ_0 and copies of a preparation of ρ_p , and outputs “reject” or “accept” is a weak-membership certification test if with high probability $\geq 1 - \alpha$ it rejects every ρ_p for which $F(\rho_p, \rho_0) \leq F_T$, and accepts every ρ_p for which $F(\rho_p, \rho_0) \geq F_T + \delta$ for some fidelity gap $\delta > 0$.*

Certification protocol

In this section, we lay out the actual certification protocol of frustration-free Hamiltonians. The anticipated state to be certified is the ground state ρ_0 of H , on which a sequence of local measurements is performed, followed by efficient classical post-processing.

Protocol 1 (Certification protocol for FF Hamiltonians).

1. Arthur chooses a threshold fidelity $F_T < 1$, maximal failure probability $1 > \alpha > 0$ and an estimation error $\epsilon \leq (1 - F_T)/2$.
2. Now Arthur asks Merlin to prepare a sufficient number of copies of the ground state ρ_0 of the frustration-free and gapped Hamiltonian $H = \sum_\lambda h_\lambda$, i.e., the unique state that fulfils $H\rho_0 = 0$.

3. Arthur measures each of the n local terms m times on the copies of the state ρ_p prepared by Merlin to determine an estimate E^* of the expectation value $\sum_\lambda \text{Tr}[\rho_p h_\lambda]$. Each measurement is performed on a new copy, and m is given by expression (5).
4. From the estimate E^* he obtains an estimate F^* of the fidelity $F = F(\rho_p, \rho_0)$ such that $F^* \in [F - \epsilon, F + \epsilon]$ with high probability.
5. If $F^* > F_T + \delta - \epsilon$ he accepts, if $F^* < F_T + \epsilon$ he rejects. Here, the fidelity gap δ is given in Eq. (1).

The subsequent proposition makes the resources needed for such a certification more precise:

Proposition 1 (Weak-membership certification). *Let $H = \sum_\lambda h_\lambda$ be a frustration-free and gapped Hamiltonian with unique ground state. Let $J = \max_\lambda \|h_\lambda\|$. Protocol 1 is a weak-membership certification test with fidelity gap*

$$\delta = \min \left\{ 1 - F_T, 2\epsilon + \frac{\langle H \rangle_{\rho_p}}{\Delta} \left(1 - \frac{\Delta}{\|H\|} \right) \right\}, \quad (1)$$

and requires

$$m \geq \frac{Jn^2}{2\Delta^2\epsilon^2} \ln \left[-\frac{n+1}{\ln(1-\alpha)} \right]. \quad (2)$$

measurements of each of the n local terms on ρ_p to determine the expectation value $\langle H \rangle_{\rho_p} = \text{Tr}[H\rho_p]$.

To estimate the difference between the estimated energy E^* and the actual ground state energy E_0 , it is crucial for our approach to have *a priori* knowledge of E_0 . By requiring H to be frustration-free, we ensure that $E_0 = 0$. However, the assumption of frustration-freeness may be dropped as long as E_0 is known.

Note that it does not matter how the measurement of the total energy $\langle H \rangle$ is performed; depending on the setup at hand, it may be more suitable to measure the energy directly rather than measure all terms individually as insinuated in Step 3 of the protocol. One major advantage of our approach is that one can perform the output measurement on the same copies as the certification measurement. This means that our certification protocol can be simply integrated in the readout protocol of a GS-QS: perform the certification measurements on the copies of ρ_p first and then use the same states for the readout measurements if the certification test accepts ρ_p .

Proof of Proposition 1

In order to show Proposition 1, we require some detail on how to estimate the global energy from measurements of local Hamiltonian terms, cast into the form of a large-deviation bound. Such a bound is given by the following Lemma, which is stated and proved along the same lines as Lemma S4 in Ref. [14].

Lemma 1 (Estimation of the energy). *Decompose the local terms in their eigen-basis: $h_\lambda = \sum_\mu e_{\lambda,\mu} P_{\lambda,\mu}$, where the $P_{\lambda,\mu}$ are orthogonal projections onto the eigenspaces corresponding to eigenvalues $e_{\lambda,\mu}$. Let $X_\lambda^{(i)}$ be the random variable that takes the value $e_{\lambda,\mu}$ with probability $\text{Tr}(\rho_p P_{\lambda,\mu})$ by the measurement of h_λ on the i^{th} copy of ρ_p . Moreover, let*

$$\langle h_\lambda \rangle_{\rho_p}^* = \frac{1}{m} \sum_{i=1}^m X_\lambda^{(i)} \quad (3)$$

be the estimate of $\langle h_\lambda \rangle$ on ρ_p by a finite-sample average of m measurement outcomes, and $\langle H \rangle_{\rho_p}^* = \sum_\lambda \langle h_\lambda \rangle_{\rho_p}^*$ the resulting estimate of $\langle H \rangle_{\rho_p}$. As above, define $J = \max_\lambda \|h_\lambda\|$. For $\bar{\alpha} \geq 1/2$ it holds that

$$\mathbb{P} \left[|\langle H \rangle_{\rho_p}^* - \langle H \rangle_{\rho_p}| \leq \epsilon \right] \geq \bar{\alpha}, \quad (4)$$

whenever

$$m \geq \frac{Jn^2}{2\epsilon^2} \ln \left[\frac{n+1}{\ln(1/\bar{\alpha})} \right]. \quad (5)$$

Proof. By Hoeffding's inequality,

$$\forall \lambda \in [n] : \mathbb{P} \left[|\langle h_\lambda \rangle_{\rho_p}^* - \langle h_\lambda \rangle_{\rho_p}| \geq \frac{\epsilon}{m} \right] \leq 2e^{-2\epsilon^2/m\|h_\lambda\|}, \quad (6)$$

since the $\{X_\lambda^{(i)}\}_\lambda$ are independent random variables and $0 \leq X_\lambda^{(i)} \leq \|h_\lambda\|$. Eq. (6) is equivalent to

$$\forall \lambda \in [n] : \mathbb{P} \left[|\langle h_\lambda \rangle_{\rho_p}^* - \langle h_\lambda \rangle_{\rho_p}| \leq \epsilon \right] \geq 1 - 2e^{-2m\epsilon^2/\|h_\lambda\|}, \quad (7)$$

and since all measurements are independent

$$\mathbb{P} \left[\forall \lambda \in [n] : |\langle h_\lambda \rangle_{\rho_p}^* - \langle h_\lambda \rangle_{\rho_p}| \leq \epsilon \right] \quad (8)$$

$$\geq \prod_\lambda \left(1 - 2e^{-\frac{2m\epsilon^2}{\|h_\lambda\|}} \right) \geq \left(1 - 2e^{-2m\epsilon^2/J} \right)^n, \quad (9)$$

resulting in

$$\mathbb{P} \left[|\langle H \rangle_{\rho_p}^* - \langle H \rangle_{\rho_p}| \leq \epsilon \right] \geq \left(1 - 2e^{-2m\epsilon^2/n^2 J} \right)^n \geq \bar{\alpha}. \quad (10)$$

Eq. (10) holds whenever

$$m \geq \frac{Jn^2}{2\epsilon^2} \ln \left[\frac{2}{1 - \bar{\alpha}^{1/n}} \right] =: m_{\text{opt}}, \quad (11)$$

where we can upper-bound m_{opt} as $m_{\text{opt}} \leq (Jn^2/2\epsilon^2) \ln[(n+1)/\ln(1/\bar{\alpha})]$ [14]. This shows the claim. $\square$

We would like to bound the error between the actual fidelity $F(\rho_0, \rho_p)$ and the estimate thereof given the energy measurement $\langle H \rangle_{\rho_p}^*$. To that end, we first upper- and lower-bound the fidelity by the expectation value $\langle H \rangle_{\rho_p}$ thereby complementing the lower bound from Ref. [20].

Lemma 2 (Bounds on the fidelity [20]). *Given a Hamiltonian H with gap $\Delta > 0$ above the unique ground state ρ_0 with energy $E_0 = 0$, and maximum energy $E_{\text{max}} = \|H\|$. Suppose $\langle H \rangle_\rho < E_1$, the energy of the first excited state, for some prepared state ρ . Then the overlap $F(\rho_0, \rho)$ of ρ with the ground state is bounded as*

$$F_{\text{max}}(\rho) := 1 - \frac{\langle H \rangle_\rho}{\|H\|} \geq F(\rho_0, \rho) \geq 1 - \frac{\langle H \rangle_\rho}{\Delta} =: F_{\text{min}}(\rho). \quad (12)$$

Proof. Decompose $H = \sum_{i=0}^n E_i |E_i\rangle\langle E_i|$. Then,

$$\begin{aligned} \|H\|(1 - \text{Tr}[\rho_0 \rho]) &= E_{\text{max}} \sum_{i>0} \langle E_i, \rho E_i \rangle \\ &\geq \text{Tr}[H\rho] \geq \Delta \sum_{i>0} \langle E_i, \rho E_i \rangle \\ &= \Delta(1 - \text{Tr}[\rho_0 \rho]), \end{aligned} \quad (13)$$

(equivalently $\|H\|(1 - P_0) \geq H \geq \Delta(1 - P_0)$, where P_0 projects onto the ground space) yielding $1 - \text{Tr}[H\rho]/\|H\| \geq F(\rho_0, \rho) \geq 1 - \text{Tr}[H\rho]/\Delta$. $\square$

Remark (Mixed quantum states). *Note that no assumptions on the prepared state ρ_p are made, in particular, it need not be pure.*

This means that the lower bound to the fidelity resulting from those estimates $F_{\text{min}}^* := F_{\text{min}}(\rho_p)^* = 1 - \langle H \rangle_{\rho_p}^*/\Delta$ obeys

$$\mathbb{P} [|F_{\text{min}}^* - F_{\text{min}}| \leq \epsilon] \geq 1 - \alpha, \quad (14)$$

with $F_{\text{min}} = F_{\text{min}}(\rho_p)$ whenever

$$m \geq \frac{Jn^2}{2\Delta^2\epsilon^2} \ln \left[-\frac{n+1}{\ln(1-\alpha)} \right]. \quad (15)$$

Proof of Proposition 1. (i) (Completeness) Let $F \geq F_T + \delta$. Then $F_{\text{max}} \geq F_T + \delta$ and thus $F_{\text{min}} \geq F_T + \delta - |F_{\text{max}} - F_{\text{min}}| = F_T + 2\epsilon$, where we have used the fidelity gap (1) and that

$$|F_{\text{max}} - F_{\text{min}}| = \left| \frac{\langle H \rangle_{\rho_p}}{\Delta} - \frac{\langle H \rangle_{\rho_p}}{\|H\|} \right|. \quad (16)$$

Hence, it follows from Eq. (14) that $\mathbb{P}[|F_{\text{min}} - F_{\text{min}}^*| \leq \epsilon] \geq 1 - \alpha$, so that $\mathbb{P}[F_{\text{min}}^* \geq F_T + \epsilon] \geq 1 - \alpha$.

(ii) (Soundness) Let ρ_p be such that $F < F_T$. It then follows that $F_{\text{min}} \leq F < F_T$. Hence,

$$\mathbb{P}[F_{\text{min}}^* < F_T + \epsilon] > 1 - \alpha \quad (17)$$

can be derived from Eq. (14) so that ρ_p is rejected with probability at least $1 - \alpha$. $\square$

Use of the bounds in analog simulation

The above techniques can readily be applied to frustration-free analog GS-QS. Indeed, many interesting Hamiltonians can be identified as frustration-free Hamiltonians in the above sense. Notably, for one-dimensional quantum systems, the parent-Hamiltonians of matrix-product states are frustration-free [26]. For two-dimensional systems, the toric code Hamiltonian [27] constitutes an important example of a Hamiltonian of this type.

This motivates the question of how such ground states of frustration-free Hamiltonians can be efficiently prepared. In the next section we discuss the preparation of ground states using an *adiabatic algorithm*. Depending on the setting other methods may prove more practical, though. For example, one can prepare the ground state by *local unitary circuit* or by *engineering dissipation*. In both of these cases, however, it is not yet fully known how to efficiently prepare ground states, unless additional conditions are satisfied. Specifically, if all local Hamiltonian terms commute, the ground state of a frustration-free Hamiltonian can be prepared efficiently using a unitary variant [28] of Moser's algorithm for solving certain classical satisfiability problems [29]. Relatedly, in Ref. [30] the authors demonstrate that some frustration-free Hamiltonians can be cooled into their ground states by engineering dissipation. In this scheme, the (possibly regrouped) local terms are individually cooled by engineering local dissipative terms suitably. If cooling one term cannot create an excitation at a different location the protocol is efficient.

Encoding quantum computations in ground states

Protocol 1 offers a convenient way to certify ground states of frustration-free Hamiltonians. To serve as proper quantum simulators, the problems solvable by means of these systems should be computationally hard, i.e., intractable on a classical computer. This is the case; indeed, one can perform universal (adiabatic) quantum computation by preparing the ground states of certain spatially local frustration-free Hamiltonian.

Proposition 2 (Encoding quantum computation in ground states [24]). *Let $U = U_L \cdots U_1$ be an arbitrary quantum circuit involving one- and two-qubit unitaries U_i , $i = 1, \dots, L$, that acts on K qubits, and $L = \text{poly}(K)$, let $|\phi_0\rangle \in (\mathbb{C}^2)^{\otimes K}$ be an initial state, and set $n = O(K^2)$.*

Then there exists a Hamiltonian $H_{ac}(\lambda)$, $0 \leq \lambda \leq 1$ on an $n \times n$ square lattice each site of which can be occupied by either zero particles or one spin-1/2 particle. For the computation, a string of $2n$ particles move through the lattice. In particular, the following holds: For all $\lambda \in [0, 1]$, $H_{ac}(\lambda)$ is polynomially gapped as $\Omega(n^{-3})$. Moreover, the evolved Hamiltonian $H_{ac}(1)$ is frustration free and has a unique ground state $|\text{gs}\rangle_{ac}$. The probability of measuring the position of the particles on $|\text{gs}\rangle_{ac}$ such that one obtains the

output state $(U_L \cdots U_1)|\phi_0\rangle$ in their spin degrees of freedom is lower bounded by a constant.

In the proof of Ref. [24] H_{ac} is constructed as a variant of the Feynman-Kitaev Hamiltonian. Specifically, the Hamiltonian H_{ac} describes the diffusion of a string of the particles on the lattice, where at each plaquette two particles interact via a four-body interaction term. That is, the position of the particle string serves as a clock register, their internal state as the work register. Proposition 2 entails that (a) the ground state of the Hamiltonian $H_{ac}(1)$ is unique, (2) can be efficiently prepared by preparing the ground state of $H_{ac}(0)$ and then tuning λ adiabatically from 0 to 1, and (c) is polynomially gapped. Finally, (d) the output of the computation can be obtained by performing measurements on the spin degrees of freedom. Thus, the ground state of $H_{ac}(1)$ can be certified by an energy measurement on $|\text{gs}\rangle_{ac}$ according to Protocol 1. More recently, it has been shown how to improve this construction to make only use of nearest-neighbour interactions [31].

In order to familiarise the reader with the construction, we here sketch the most basic variant [23] of the Feynman-Kitaev clock construction [32–34]. In this construction, the discrete evolution under a quantum circuit is mapped to measuring the ground state of a local frustration-free Hamiltonian called the Feynman-Kitaev Hamiltonian. The discretised time evolution $(U_L \cdots U_2 U_1)|\phi_0\rangle_w$ of a k -qubit input state vector $|\phi_0\rangle_w$ is in this setting mapped onto a so-called *history state*

$$|\psi_{\text{hist}}\rangle = \frac{1}{\sqrt{L+1}} \sum_{t=0}^L (U_t \cdots U_0 |\phi_0\rangle_w) \otimes |t\rangle_c, \quad (18)$$

of a bipartite system comprising a work and a clock register. The work register consists of k qubits, the clock-register is an L -dimensional quantum system with state vectors $\{|t\rangle\}_{t=0}^L$. The combined system is equipped with a Hilbert space $\mathcal{H}_{\text{work}} \otimes \mathcal{H}_{\text{clock}} \cong (\mathbb{C}^2)^{\otimes k} \otimes \mathbb{C}^L$ [35]. The history state is the ground state of a Hamiltonian that selects configurations for which the work register is updated correctly as the clock proceeds in time. Such a Hamiltonian has the form

$$H_{\text{update}} = \sum_{t=1}^L U_t \otimes |t\rangle\langle t-1|_c + U_t^\dagger \otimes |t-1\rangle\langle t|_c. \quad (19)$$

Whenever the clock undergoes a transition from $|t\rangle$ to $|t+1\rangle$, the unitary map U_t is applied to the work register. The computation U_t is undone via the application of $U_t^\dagger$ as the clock transits from $|t+1\rangle$ to $|t\rangle$. This Hamiltonian is of the form of a quantum walk on the line of state vectors $|\psi_t\rangle = (U_t \cdots U_0 |\phi_0\rangle_w) \otimes |t\rangle_c$. In each state vector $|\psi_t\rangle$ the computation up to step t is stored in the work register as well as a time-marker in the clock register. The full Hamiltonian consists of an additional term H_{input} that select the correct input configuration. Moreover, the highly non-local clock terms can be made strictly local using the construction of a unary clock in which the state vector $|t\rangle$ is represented by an L -qubit state

vector

$$|t'\rangle = |\underbrace{1, \dots, 1}_t, \underbrace{0, \dots, 0}_{L-t}\rangle. \quad (20)$$

The correct configurations of such a clock are enforced by another additional term H_{clock} . The full Feynman-Kitaev Hamiltonian then reads

$$H_{\text{FK}} = H_{\text{input}} + H_{\text{update}} + H_{\text{clock}}. \quad (21)$$

The output of the computation can be obtained by measuring the clock register first, and then measuring the work register [36]. In order to raise the probability of obtaining outcome L upon the clock measurement from $1/(L+1)$ to a constant, one can simply introduce another $O(L)$ identity gates after the last step of the computation.

The Hamiltonian (21) is gapped as $\Delta \propto 1/L^2$, it is 5-local (but not geometrically local), and frustration-free with vanishing ground state energy, since all terms can be chosen as projections. The ground state can be prepared, for example, by adiabatically turning on the updating term H_{update} [23]. If the preparation procedure starts out in the ground space manifold, and the adiabatic path is sufficiently smooth the adiabatic theorem tells us that eventually one ends up in the ground state of the final Hamiltonian H_{update} in a time that scales as $1/\Delta^3$ [37].

Finally, note that Proposition 2 implies that arbitrary unitary and dissipative time-evolution can be simulated efficiently using the ground states of frustration-free and gapped Hamiltonians on a lattice. This is the case because arbitrary local Lindbladian dynamics can be approximated by a polynomial length quantum circuit and thus simulated efficiently on a quantum computer [38].

Towards quantum supremacy

In the previous section we have discussed a general mapping of quantum circuits to unique ground states of frustration-free, poly-gapped local Hamiltonians. In this section we will specialise to the family of circuits proposed by Bremner, Montanaro, and Shepherd [21], for which there is strong complexity-theoretic evidence (in contrast to Shor's algorithm) that their output probability distribution is hard to simulate on any classical computer within an error of $1/192$ in total variation distance. While this result on its own is remarkable, one might question whether the "theoretically hard" quantum state has actually been prepared in an experiment. However, using our certification result, one can indeed *certify* the sufficiently precise preparation of a quantum state, such that measurements in the Z -basis are intractable for classical computers under a plausible complexity-theoretic conjecture. This significantly strengthens the perspective to experimentally demonstrate *quantum supremacy* [22].

The result of Ref. [21] is based on the conjectured average-case hardness to compute the *gap* of degree-3 polynomials

over $\mathbb{F}_2$, $f : \{0, 1\}^n \rightarrow \{0, 1\}$, which can be written (up to an additive constant) as

$$f(x) = \sum_{i,j,k} \alpha_{i,j,k} x_i x_j x_k + \sum_{i,j} \beta_{i,j} x_i x_j + \sum_i \gamma_i x_i \pmod{2}, \quad (22)$$

where $\alpha_{i,j,k}, \beta_{i,j}, \gamma_i \in \{0, 1\}$ and the gap is defined as $\text{gap}(f) = |\{x | f(x) = 0\}| - |\{x | f(x) = 1\}|$. Let the normalised gap be $\text{ngap}(f) = \text{gap}(f)/2^n$. Then the following is assumed to be true.

Conjecture 1 ([21]). *Let $f : \{0, 1\}^n \rightarrow \{0, 1\}$ be a uniformly random degree-3 polynomial over $\mathbb{F}_2$. Then it is $\#P$ -hard to approximate $\text{ngap}(f)^2$ up to multiplicative error of $1/4 + o(1)$ for a $1/24$ fraction of polynomials f .*

While Conjecture 1 is not known to hold for an *uniformly random* choice of polynomials, it is known to be true in the *worst case* [39]. All that is left to show is how to lift this result from worst-case to average-case hardness.

The gap as defined above can be expressed conveniently as the acceptance probability of a family $\mathcal{C}_f$ of so-called IQP circuits on n qubits, which has the following structure: (i) apply Hadamard gates on all qubits, (ii) apply a sequence of Z , CZ , CCZ gates (encoding the terms of $f(x)$), (iii) apply Hadamard gates on all qubits again. That is, $\text{ngap}(f) = \langle 0|^{\otimes n} \mathcal{C}_f | 0 \rangle^{\otimes n}$. Note for experimental simplicity, that all the diagonal gates commute and the circuit has only constant depth.

We are now ready to state the result of Bremner, Montanaro, and Shepherd precisely:

Theorem 1 ([21]). *Assume Conjecture 1 is true. If it is possible to classically sample from the output probability distribution of any IQP circuit C in polynomial time, up to an error of $1/192$ in ℓ_1 norm, then there is a BPP^{NP} algorithm to solve any problem in $P^{\#P}$. Hence the Polynomial Hierarchy would collapse to its third level.*

For space reasons, we cannot introduce the Polynomial Hierarchy here, suffice it to note its central importance in computational complexity theory as a generalisation of the better-known $P \neq NP$ conjecture.

Theorem 1 requires to prepare the output distribution of an IQP circuit with error of $1/192$ in ℓ_1 norm. We propose to *implement and certify* this assumption by the following procedure. Let L be the number of gates in an IQP circuit.

1. Map the IQP circuit to the ground state ρ_0 of a frustration-free, gapped, local Hamiltonian, e.g., according to Proposition 2 and choose m according to Eq. (5)
2. Flip a fair coin to decide for either (a) or (b):
 - (a) Prepare the ground state ρ_p of this local Hamiltonian adiabatically m times, measure local Hamiltonian terms to certify an upper bound on $\|\rho_0 - \rho_p\|_1 \leq \varepsilon$, or

- (b) Prepare the ground state ρ_p and measure the position of all spins which projects on the output state of the IQP circuit ρ_I with constant probability (otherwise, repeat the step), then measure all qubits in the Z basis.

Step 2a certifies, that the quantum simulator indeed prepares a state ρ_p such that $\|\rho_0 - \rho_p\|_1 \leq \varepsilon(m)$. The ideal ground state ρ_0 of the Hamiltonian described in Proposition 2 has constant overlap with the output state of the IQP circuit ρ_I , i.e., $\|\rho_0 - \rho_I\|_1 \leq c$, which can therefore be projected with constant probability on the subspace where the computation has completed by measuring the respective terms of the Hamiltonian, i.e.,

$$\rho_I = \frac{\Pi \rho_0 \Pi}{\text{Tr}(\Pi \rho_0)}. \quad (23)$$

Similarly, we project in step 2b the physically prepared state

$$\rho_{I,p} = \frac{\Pi \rho_p \Pi}{\text{Tr}(\Pi \rho_p)}. \quad (24)$$

It follows by the triangle inequality and properties of the trace distance, that

$$\|\rho_I - \rho_{I,p}\|_1 \leq \frac{2}{c} \|\rho_0 - \rho_p\|_1 \leq \frac{2}{c} \varepsilon(m), \quad (25)$$

which can be driven below the required constant of $1/192$ by an appropriate choice of m .

Thus, we can clearly *certify* that a state has been prepared with sufficient precision (i.e., within $1/192$ in total variation distance [40]) such that measuring the first n qubits in the Z basis results in a probability distribution from which it is hard to sample from classically by Theorem 1.

Summary and discussion

In this work, we have discussed in what sense weak-membership variants of the certification of ground states of frustration-free Hamiltonians can be used to certify the correctness of analog quantum simulation and instances of quantum computation. For this certification to be possible, merely

local Hamiltonian terms have to be measured, in a way that is perfectly experimentally possible on a number of platforms, in conjunction with efficient classical processing. No multi-round interactive proof systems is required for that. The results here challenge the view that is often expressed specifically in the physics literature, namely that in order to certify a quantum simulator, one needs to be able to efficiently keep track of the outcome of the simulation. Instead, in important cases, one can certify its functioning without being able to efficiently predict the actual result of the simulation. The discussion of universal quantum computing is in this context is primarily relevant to show that on a classical device computationally hard problems can indeed be solved by analog quantum simulators.

Having said this, the observations made here further motivate the quest of identifying further intermediate problems. Such an intermediate problem would satisfy two criteria:

- (1) The problem is believed to be intractable classically, but it is not necessarily the case that arbitrary quantum computations can be reduced to solving it.
- (2) A reliable quantum simulator is conceivable that can be practically realised with present day experimental capacities and solves that problem.

Identifying such problems requires a complexity-theoretic analysis of problems that are related to physical models. Notions of boson sampling offer interesting instances of intermediate problems [41–43]. As an illustration of our approach we have sketched how our method can be combined with the results of Ref. [21] to certify the preparation of a probability distribution, which is provably hard to simulate on any classical computer under a plausible complexity-theoretic assumption.

Acknowledgements

We would like to thank M. Gluza, D. Gosset, and B. M. Terhal for discussions and the EU (AQuS, SIQS, RAQUEL), the COST network, the ERC (TAQ), the Studienstiftung des Deutschen Volkes, and the Humboldt Foundation for support.

[1] P. W. Shor. Algorithms for quantum computation: discrete logarithms and factoring. *Proc. 50th Ann. Symp. Found. Comp. Sc.*, 1994.

[2] J. I. Cirac and P. Zoller. Goals and opportunities in quantum simulation. *Nature Phys.*, 8:264, 2012.

[3] R. P. Feynman. Simulating physics with computers. *Int. J. Th. Phys.*, 21:467, 1982.

[4] I. Bloch, J. Dalibard, and S. Nascimbene. Quantum simulations with ultracold quantum gases. *Nature Phys.*, 8:267, 2012.

[5] R. Blatt and C. F. Roos. Quantum simulations with trapped ions. *Nature Phys.*, 8:277, 2012.

[6] A. A. Houck, H. E. Türeci, and J. Koch. On-chip quantum simulation with superconducting circuits. *Nature Phys.*, 8:292, 2012.

[7] M. Köhl, H. Moritz, T. Stöferle, K. Günter, and T. Esslinger. Fermionic atoms in a three dimensional optical lattice: Observing fermi surfaces, dynamics and interactions. *Phys. Rev. Lett.*, 94:080403, 2005.

- [8] L. Tagliacozzo, A. Celi, P. Orland, M. W. Mitchell, and M. Lewenstein. Simulations of non-Abelian gauge theories with optical lattices. *Nature Comm.*, 4:2615, 2013.
- [9] J. Eisert, M. Friesdorf, and C. Gogolin. Quantum many-body systems out of equilibrium. *Nature Phys.*, 11:124–130, 2015.
- [10] S. Trotzky, Y.-A. Chen, A. Flesch, I. P. McCulloch, U. Schollwoeck, J. Eisert, and I. Bloch. Probing the relaxation towards equilibrium in an isolated strongly correlated one-dimensional Bose gas. *Nature Phys.*, 8:325, 2012.
- [11] D. Aharonov, M. Ben-Or, and E. Eban. Interactive proofs for quantum computations. In *Proc. Innov. Comp. Sc.*, page 253. Tsinghua University Press, 2010.
- [12] J. F. Fitzsimons and E. Kashefi. Unconditionally verifiable blind computation, 2012. arXiv:1203.5217.
- [13] J. F. Fitzsimons and M. Hajdusek. Post hoc verification of quantum computation, 2015. arXiv:1512.04375.
- [14] L. Aolita, C. Gogolin, M. Kliesch, and J. Eisert. Reliable quantum certification for photonic quantum technologies. *Nature Comm.*, 6:8498, 2015.
- [15] B. W. Reichardt, F. Unger, and U. U. Vazirani. A classical leash for a quantum system: Command of quantum systems via rigidity of CHSH games. arXiv:1209.0448, 2012.
- [16] B. W. Reichardt, F. Unger, and U. Vazirani. Classical command of quantum systems. *Nature*, 496:456–460, 2013.
- [17] N. Wiebe, C. Granade, C. Ferrie, and D. G. Cory. Hamiltonian learning and certification using quantum resources. *Phys. Rev. Lett.*, 112:190501, 2014.
- [18] N. Wiebe, C. Granade, C. Ferrie, and D. G. Cory. Quantum Hamiltonian learning using imperfect quantum resources. *Phys. Rev. A*, 89:042314, 2014.
- [19] N. Wiebe, C. Granade, and D. G. Cory. Quantum bootstrapping via compressed quantum Hamiltonian learning. *New J. Phys.*, 17:022005, 2015.
- [20] M. Cramer, M. B. Plenio, S. T. Flammia, R. Somma, D. Gross, S. D. Bartlett, O. Landon-Cardinal, D. Poulin, and Y.-K. Liu. Efficient quantum state tomography. *Nat. Comm.*, 1:149, 2010.
- [21] M. J. Bremner, A. Montanaro, and D. J. Shepherd. Average-case complexity versus approximate simulation of commuting quantum computations. arXiv:1504.07999, 2015.
- [22] J. Preskill. Quantum computing and the entanglement frontier. *Bull. Am. Phys. Soc.*, 58, 2013.
- [23] S. Bravyi and B. M. Terhal. Complexity of stoquastic frustration-free Hamiltonians. *SIAM J. Comp.*, 39(4):1462–1485, 2010.
- [24] D. Gosset, B. M. Terhal, and A. Vershynina. Universal adiabatic quantum computation via the space-time circuit-to-hamiltonian construction. *Phys. Rev. Lett.*, 114(14), 2015.
- [25] D. Aharonov, W. van Dam, J. Kempe, Z. Landau, S. Lloyd, and O. Regev. Adiabatic quantum computation is equivalent to standard quantum computation. *SIAM Rev.*, 50(4):755–787, Jan 2008.
- [26] D. Perez-Garcia, F. Verstraete, M. M. Wolf, and J. I. Cirac. Matrix product state representations. *Quant. Inf. Comput.*, 7:401, 2007.
- [27] A. Y. Kitaev. Anyons in an exactly solved model and beyond. *Ann. Phys.*, 321:2, 2006.
- [28] M. Schwarz, T. S. Cubitt, and F. Verstraete. An information-theoretic proof of the constructive commutative quantum Lovász local lemma. *CoRR*, abs/1311.6474, 2013.
- [29] R. A. Moser. A constructive proof of the Lovász Local Lemma. In *Proceedings of the Forty-first Annual ACM Symposium on Theory of Computing, STOC '09*, pages 343–350, New York, NY, USA, 2009. ACM.
- [30] F. Verstraete, M. M. Wolf, and J. I. Cirac. Quantum computation and quantum-state engineering driven by dissipation. *Nature Phys.*, 5(9):633–636, Jul 2009.
- [31] S. Lloyd and B. Terhal. Adiabatic and Hamiltonian computing on a 2D lattice with simple 2-qubit interactions. *Preprint arXiv:1509.01278*, 2015.
- [32] R. P. Feynman. Quantum mechanical computers. *Found. Phys.*, 16(6):507–531, 1986.
- [33] A. Y. Kitaev, A. Shen, and M. N. Vyalyi. *Classical and quantum computation*, volume 47. Am. Math. Soc., 2002.
- [34] D. Aharonov and T. Naveh. Quantum NP – a survey. arXiv:quant-ph/0210077, 2002.
- [35] D. Nagaj. Fast universal quantum computation with railroad-switch local Hamiltonians. *J. Math. Phys.*, 51(6):062201, 2010.
- [36] In the spatially local construction of Ref. [24] the position measurement of the particle string has the same effect.
- [37] S. Jansen, M.-B. Ruskai, and R. Seiler. Bounds for the adiabatic approximation with applications to quantum computation. *J. Math. Phys.*, 48(10):102111, 2007.
- [38] M. Kliesch, T. Barthel, C. Gogolin, M. Kastoryano, and J. Eisert. Dissipative quantum Church-Turing theorem. *Phys. Rev. Lett.*, 107:120501, 2011.
- [39] A. Ehrenfeucht and M. Karpinski. The computational complexity of (xor, and)-counting problems. In *Proc. 12th Annual ACM-SIAM Symposium on Discrete Algorithms (SODA)(2001)*, 1990.
- [40] Note that the quantum states being close in trace distance also implies closeness of the measurement distributions.
- [41] S. Aaronson and A. Arkhipov. The computational complexity of linear optics, 2011. arXiv:1011.3245.
- [42] C. Gogolin, M. Kliesch, L. Aolita, and J. Eisert. BosonSampling in the light of sample complexity, 2013. arXiv:1306.3995.
- [43] S. Aaronson and A. Arkhipov. BosonSampling is far from uniform, 2013. arXiv:1309.7460.